CAR & PASSENGER VEHICLE

Century Car & Passenger vehicle batteries are built tough to provide the ultimate in battery performance and reliability. Featuring internal components which are designed from the ground up to suit Australian conditions, unique design features and industry leading technologies to combat the causes of battery failure, Century Ultra Hi Performance and Hi Performance batteries deliver reliability, longer life and superior performance.


Manufactured with Calcium battery plates, advanced grid designs, optimised paste formulation and our own revolutionary maintenance free lid technology, Century Car & Passenger vehicle batteries deliver superior starting power, exceptional corrosion resistance, longer life and the performance to handle the demands of today's modern vehicles.

Hi Performance DIN

Century Hi Performance DIN batteries have been designed and manufactured to deliver longer life and performance while meeting the fitment requirements of imported vehicles. Suitable for both old and new vehicles with standard power demands, Century Hi Performance DIN batteries are engineered to meet leading vehicle manufacturer's standards for quality and performance, delivering superior starting power, longer service life and power to run vehicle electrics.

- ✓ Suitable replacement for original equipment (OE) batteries
- Suitable for both old and new vehicles with standard power demands
- Designed and built tough in Australia to suit our local conditions[^]
- Longer service life with a sealed maintenance free design for reduced water loss

ITEM ID	ВАТТЕRY ТҮРЕ	WARRANTY [†]	ΛΟΓΤS	CCA -18⁰C	RC @ 25°C	AH @ 20HR	(ALL M	L L EASURE	ра TH Lw MENTS H	-	-+	KG	TERM. TYPE		SPECIAL FEATURES
HI PE	HI PERFORMANCE DIN														
115130	DIN44L MF	30	12	420	70	43	208	175	175	175	С	11.50	STD	SIDE/ END	CH, CI, CV, FA, MF, RP, VR
115145	DIN44LH MF	30	12	420	85	50	208	175	190	190	С	11.50	STD	SIDE/ END	CH, CI, CV, FA, MF, RP, VR
115131	DIN53L MF	30	12	500	90	54	242	175	175	175	С	13.50	STD	SIDE/ END	CH, CI, CV, FA, MF, RP, VR
115132	DIN53LH MF	30	12	500	90	55	242	175	190	190	С	14.00	STD	SIDE/ END	CH, CI, CV, FA, MF, RP, VR
115133	DIN53R MF	30	12	500	90	54	242	175	175	175	D	13.50	STD	SIDE/ END	CH, CI, CV, FA, MF, RP, VR
115134	DIN65L MF	30	12	580	110	63	277	175	175	175	С	15.50	STD	SIDE/ END	CH, CI, CV, FA, MF, RP, VR
115136	DIN65R MF	30	12	580	110	63	277	175	175	175	D	15.50	STD	SIDE/ END	CH, CI, CV, FA, MF, RP, VR
112112	DIN65LH MF	30	12	660	130	68	277	175	190	190	С	18.40	STD	SIDE/ END	CH, CI, CV, FA, MF, MIA, MR, RP
112113	DIN65RH MF	30	12	660	130	68	277	175	190	190	D	18.40	STD	SIDE/ END	CH, CI, CV, FA, MF, MIA, MR, RP
115137	DIN75L MF	30	12	730	135	80	315	175	175	175	С	18.00	STD	SIDE/ END	CH, CI, CV, FA, MF, RP, VR
115147	DIN75LH MF	30	12	750	160	90	315	175	190	190	С	20.90	STD	SIDE/ END	CH, CI, CV, FA, MF, RP
115148	DIN75RH MF	30	12	750	160	90	315	175	190	190	D	20.90	STD	SIDE/ END	CH, CI, CV, FA, MF, RP
115138	DIN85L MF	30	12	780	158	85	353	175	175	175	С	20.00	STD	SIDE/ END	CH, CI, CV, FA, MF, RP, VR
115139	DIN85LH MF	30	12	760	165	88	353	175	190	190	С	21.50	STD	SIDE/ END	CH, CI, CV, FA, MF, RP, VR
115146	DIN110LH MF	30	12	920	195	110	393	175	190	190	С	25.00	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR









† Conditions apply. Refer to individual warranty statements attached to each battery. ^Selected items only.