



# CAR & PASSENGER VEHICLE

YUASA CAR AND PASSENGER VEHICLE BATTERIES ARE THE ULTIMATE IN BATTERY PERFORMANCE AND MAINTENANCE FREE TECHNOLOGY. FEATURING SPECIALIST INTERNAL COMPONENTS, UNIQUE DESIGN FEATURES AND INDUSTRY LEADING TECHNOLOGIES TO COMBAT THE CAUSES OF BATTERY FAILURE AND DELIVER RELIABILITY, LONGER LIFE AND SUPERIOR PERFORMANCE.

Manufactured with Calcium battery plates, advanced grid designs, optimised paste formulation and our own revolutionary maintenance free lid technology, Yuasa Car & Passenger vehicle batteries deliver superior starting power, exceptional corrosion resistance, longer life and the performance to handle the demands of today's modern vehicles.




## POWER SERIES DIN

Yuasa Power Series DIN batteries have been designed and manufactured to deliver longer life and performance while meeting the fitment requirements of imported vehicles. Suitable for both old and new vehicles with standard power demands, Yuasa Power Series DIN batteries are engineered to meet leading vehicle manufacturer's standards for quality and performance, delivering superior starting power, longer service life and power to run vehicle electrics.



- ➔ Suitable replacement for original equipment (OE) batteries
- ➔ Suitable for both old and new vehicles with standard power demands
- ➔ Designed and built tough in Australia to suit our local conditions<sup>^</sup>
- ➔ Longer service life with a sealed maintenance free design for reduced water loss

ITEM ID	BATTERY TYPE	WARRANTY†	VOLTS	CCA -18°C	RC @ 25°C	AH @ 20HR	Dimensions (all measurements in mm)				POLARITY	WEIGHT (KG)	TERM. TYPE	HOLD DOWN	SPECIAL FEATURES
							L	W	H	TH					
POWER SERIES DIN															
115212	DIN44L MF	30	12	420	70	43	208	175	175	175	C	11.50	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR
115227	DIN44LH MF	30	12	420	85	50	208	175	190	190	C	11.50	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR
115213	DIN53L MF	30	12	500	90	54	242	175	175	175	C	13.50	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR
115214	DIN53LH MF	30	12	500	90	55	242	175	190	190	C	14.00	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR
115215	DIN53R MF	30	12	500	90	54	242	175	175	175	D	13.50	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR
115216	DIN65L MF	30	12	580	110	63	277	175	175	175	C	15.50	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR
112202	DIN65LH MF	30	12	660	130	68	277	175	190	190	C	18.40	STD	SIDE/END	CH, CI, CV, FA, MF, MIA, MR, RP
115217	DIN65R MF	30	12	580	120	63	277	175	175	175	D	15.50	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR
112203	DIN65RH MF	30	12	660	130	68	277	175	190	190	D	18.40	STD	SIDE/END	CH, CI, CV, FA, MF, MIA, MR, RP
115218	DIN75L MF	30	12	730	135	80	315	175	175	175	C	18.00	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR
115232	DIN75LH MF	30	12	750	160	90	315	175	190	190	C	20.90	STD	SIDE/END	CH, CI, CV, FA, MF, RP
115231	DIN75RH MF	30	12	750	160	90	315	175	190	190	D	20.90	STD	SIDE/END	CH, CI, CV, FA, MF, RP
115219	DIN85L MF	30	12	780	158	85	353	175	175	175	C	20.00	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR
115220	DIN85LH MF	30	12	760	165	88	353	175	190	190	C	21.50	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR
115229	DIN110LH MF	30	12	920	195	110	393	175	190	190	C	25.00	STD	SIDE/END	CH, CI, CV, FA, MF, RP, VR



† Conditions apply. Refer to individual warranty statements attached to each battery.  
<sup>^</sup> Selected items only.

