

CAR & PASSENGER VEHICLE



POWER SERIES ULTRA

Yuasa Power Series Ultra batteries are designed and built in Australia[^] to suit our local conditions, providing the ultimate in battery performance. Suitable for both old and new vehicles with higher power demands, Yuasa Power Series Ultra batteries are engineered to exceed leading vehicle manufacturer's standards for quality and performance, delivering exceptional starting power, maximum service life and extra power for vehicle electrics.



Over 20% extra starting power and 30% longer life*

Designed and built tough in Australia[^] to suit our local conditions

Maximum service life with a sealed maintenance free design for reduced water loss













ITEM ID	ВАТТЕКҮ ТҮРЕ	WARRANTY⁺	VOLTS	CCA -18°C	RC @ 25°C	AH @ 20HR	(all measurements in mm)				• •	KG			
	BA.	>				•	L	w	Н	тн	POLARITY	WEIGHT	TERM. TYPE	HOLD DOWN	SPECIAL FEATURES
POWER SERIES ULTRA															
107220	67 MF	40	12	640	115	64	231	171	184	205	D	15.60	STD	SIDE/END	CH, CI, CV, FA, MF, MIA, MR
107221	67EF MF	40	12	640	115	64	231	171	184	208	D	15.60	STD	-	CH, CI, CV, FA, MF, MIA, MR
107222	68 MF	40	12	640	115	64	231	171	184	205	С	15.60	STD	SIDE/END	CH, CI, CV, FA, MF, MIA, MR
107224	75D23L MF	40	12	620	120	70	231	171	202	225	С	16.80	STD	SIDE	CH, CI, CV, FA, MF, MIA, MR
107223	75D23R MF	40	12	620	120	70	231	171	202	225	D	16.80	STD	SIDE	CH, CI, CV, FA, MF, MIA, MR
107226	NS40ZLX MF	40	12	410	65	42	196	128	201	220	С	10.90	SP	-	CH, CI, CV, FA, MF, MIA, MR
107228	NS40ZLSX MF	40	12	410	65	42	196	128	201	220	С	10.90	STD	-	CH, CI, CV, FA, MF, MIA, MR
107232	NS60LSX MF	40	12	480	80	50	235	128	201	220	С	12.70	STD	-	CH, CI, CV, FA, MF, MIA, MR
107231	NS60SX MF	40	12	480	80	50	235	128	201	220	D	12.70	STD	-	CH, CI, CV, FA, MF, MIA, MR
POWE	POWER SERIES ULTRA DIN														
113206	DIN65LHX MF	40	12	760	145	77	277	175	190	190	С	19.50	STD	SIDE/END	CH, CI, CV, FA, MF, MIA, MR, RP
113207	DIN65RHX MF	40	12	760	145	77	277	175	190	190	D	19.50	STD	SIDE/END	CH, CI, CV, FA, MF, MIA, MR, RP
109204	DIN75LHX MF	40	12	910	180	90	315	175	190	190	С	21.30	STD	SIDE/END	CH, CI, CV, FA, MF, RP
109205	DIN75RHX MF	40	12	910	180	90	315	175	190	190	D	21.30	STD	SIDE/END	CH, CI, CV, FA, MF, RP



†Conditions apply. Refer to individual warranty statements attached to each battery.
*Based on NS40ZLX MF and NS40ZL MF. ^Selected items only.

