



ISS ACTIVE AGM & EFB

YUASA'S ISS ACTIVE BATTERY RANGE REPRESENTS THE LATEST IN PERFORMANCE & TECHNOLOGY FOR IDLE STOP START SYSTEMS.

Yuasa ISS Active batteries are specially designed to satisfy the fuel saving and emission reducing benefits of vehicles fitted with Idle Stop Start systems.

The range incorporates innovative design features and advanced raw materials to deliver superior cycling performance, high charge acceptance for rapid recharge in between engine off modes and the extra power to run on-board electrics whilst the engine is switched off.



ISS ACTIVE

ISS ACTIVE EFB


A range of original equipment (OE) grade Enhanced Flooded Batteries (EFB) which are used and endorsed by some of the world's leading car brands. The ISS Active EFB range is designed to help reduce fuel consumption and CO₂ emissions in vehicles fitted with standard Idle Stop Start systems.



- Direct OE replacement - perfect for replacing your vehicle's original equipment battery*
- Lithium carbon additive for up to 50% faster recharging and 2x higher cycling performance
- Thicker and stronger internal components for increased shock and vibration resistance
- Recommended upgrade for standard vehicles subjected to repeated short journeys



ITEM ID	BATTERY TYPE	WARRANTY†	VOLTS	CCA -18°C	RC @ 25°C	AH @ 20HR	Dimensions (all measurements in mm)				POLARITY	WEIGHT (KG)	TERM. TYPE	HOLD DOWN	SPECIAL FEATURES
							L	W	H	TH					
ISS ACTIVE EFB															
106220	Q85	36	12	650	112	67	232	173	200	225	C	18.20	STD	-	EFB, LI, LM
106210	Q85R	36	12	650	113	67	232	171	200	225	D	18.30	STD	-	CH, CI, EFB, LI, LM
106211	S95	36	12	760	127	68	260	173	200	225	C	19.40	STD	-	EFB, LI, LM
106201	T110	36	12	810	155	80	303	173	200	225	C	23.30	STD	-	EFB, LI, LM
ISS ACTIVE EFB MF															
116200	Q85 MF	24	12	550	110	65	230	171	202	222	C	17.00	STD	-	CH, CI, EFB, FA, MF
116210	Q85R MF	24	12	550	110	65	230	171	202	222	D	17.00	STD	-	CH, CI, EFB, FA, MF
116211	S95 MF	24	12	680	130	70	258	172	199	220	C	19.90	STD	-	CH, CI, EFB, FA, MF
116201	T110 MF	24	12	760	150	95	302	170	200	222	C	22.50	STD	SIDE	CH, CI, EFB, FA, MF
116212	DIN53LH EFB	24	12	560	100	60	242	175	190	190	C	16.50	STD	SIDE/END	CH, EFB, FA, MF, RP
106216	DIN65L EFB	24	12	650	110	65	275	175	175	175	C	17.00	STD	SIDE/END	CH, EFB, FA, MF, RP
116213	DIN65LH EFB	24	12	650	120	70	275	175	190	190	C	19.10	STD	SIDE/END	CH, EFB, FA, MF, RP
106217	DIN75L EFB	24	12	730	135	75	313	175	175	175	C	19.10	STD	SIDE/END	CH, EFB, FA, MF, RP
116214	DIN75LH EFB	24	12	730	145	80	313	175	190	190	C	21.20	STD	SIDE/END	CH, EFB, FA, MF, RP



†Conditions apply. Refer to individual warranty statements attached to each battery.
*Selected vehicles only.