



YuMicron

YuMicron batteries are designed to meet the special demands of personal watercraft, snowmobiles and ATVs. Dependable power, reduced maintenance and longer life plus a unique power boosting design makes the YuMicron range ideal for touring bikes and modified vehicles.

- » Up to 30% more cranking power[#]
- » Low self-discharge and water loss for longer life
- » Polyethylene leaf with bonded glass mat – withstands vibration
- » Sulfate Stop additive to resist the effects of undercharging

ITEM ID	BATTERY TYPE	CCA -18°C*	AH @ 10HR	DIMENSIONS in MM (±2 mm)			WEIGHT WITH ACID (KG)	ACID VOLUME (L)	CHARGE CURRENT (AMPS)	TERMINAL TYPE (SEE PG13)	ASSEMBLY FIGURE
				L	W	H					
YUMICRON (SUPPLIED DRY CHARGED)											
155066	YB3L-A	32	3	98	56	110	1.3	0.24	0.3	6	
155067	YB3L-B	32	3	98	56	110	1.3	0.24	0.3	6	
155068	YB4L-A	56	4	120	70	92	1.5	0.3	0.4	5	
155069	YB4L-B	56	4	120	70	92	1.5	0.3	0.4	5	
155070	YB5L-B	65	5	120	60	130	2	0.36	0.5	6	
155071	YB7-A	124	8	135	75	133	3	0.6	0.8	6	
155072	YB7B-B	115	7	150	60	130	3.1	0.5	0.7	6	
155073	YB7C-A	124	8	130	90	114	3	0.6	0.8	3	
155074	YB7L-B	124	8	135	75	133	2.9	0.6	0.8	6	
155075	YB9A-A	124	9	135	75	155	3.1	0.6	0.9	6	
155077	YB9L-A2	124	9	135	75	139	3.1	0.6	0.9	2	
155076	YB9-B	130	9	135	75	139	3.1	0.6	0.9	6	
155078	YB9L-B	130	9	135	75	139	3.1	0.6	0.9	6	
155039	YB10A-A2	160	11	135	90	155	4	0.8	1.1	8	
155040	YB10L-A2	160	11	135	90	145	4.2	0.8	1.1	8	
155041	YB10L-B	160	11	135	90	145	4	0.8	1.1	6	

ITEM ID	BATTERY TYPE	CCA -18°C*	AH @ 10HR	DIMENSIONS in MM (±2 mm)			WEIGHT WITH ACID (KG)	ACID VOLUME (L)	CHARGE CURRENT (AMPS)	TERMINAL TYPE (SEE PG13)	ASSEMBLY FIGURE
				L	W	H					
YUMICRON CONTINUED (SUPPLIED DRY CHARGED)											
155042	YB10L-B2	160	11	135	90	145	4	0.8	1.1	8	
155043	YB12A-A	165	12	134	80	160	4.1	0.8	1.2	6	
155046	YB12AL-A	165	12	134	80	160	4	0.75	1.2	6	
155047	YB12AL-A2	165	12	134	80	160	4	0.75	1.2	8	
155045	YB12A-B	165	12	134	80	160	4	0.75	1.2	6	
155048	YB12B-B2	165	12	160	90	130	4	0.8	1.2	8	
155049	YB12C-A	165	12	134	80	175	4.3	0.8	1.2	4	
155050	YB14-A2	190	14	134	89	166	4.6	0.9	1.4	8	
155053	YB14-B2	190	14	134	89	166	4.6	0.9	1.4	8	
155051	YB14A-A1	190	14	134	89	176	4.5	0.9	1.4	6	
155052	YB14A-A2	190	14	134	89	176	4.5	0.9	1.4	8	
155054	YB14L-A2	190	14	134	89	166	4.6	0.9	1.4	8	
155055	YB14L-B2	190	14	134	89	166	4.6	0.9	1.4	8	
155056	YB16AL-A2	200	16	207	71.5	164	5.3	1.1	1.6	2	
155057	YB16-B	240	19	175	100	155	6.3	1.2	1.9	6	
155062	YB16L-B	240	19	175	100	155	6.3	1.2	1.9	6	
155058	YB16B-A	207	16	160	90	161	5.1	1	1.6	4	
155060	YB16CL-B	240	19	175	100	175	6.1	1.2	1.9	5	
155063	YB18L-A	235	18	180	90	162	5.8	1.2	1.8	7	
155034	Y50-N18A-A	260	20	205	90	176	6.5	1.5	2	7	
155035	Y50-N18L-A3	260	20	205	90	162	7.4	1.4	2	4	
155037	Y60-N24-A	300	28	184	124	175	8.6	1.7	2.8	3	
155038	Y60-N24L-A	300	28	184	124	175	8.6	1.7	2.8	3	
155065	YB30L-B	300	30	168	132	176	8.5	1.7	3	4	
155064	YB30CL-B	300	30	168	132	192.2	8.8	1.7	3	4	
155079	YHD-12H	240	28	206	133	165	8.3	2.2	2.8	9	

*CCA [Cold Cranking Amps] rating is for reference only. CCA is a theoretically calculated value. Actual performance may vary due to test conditions.
[#]When compared to equivalent conventional batteries. [#]When compared to equivalent conventional type battery.

*CCA [Cold Cranking Amps] rating is for reference only. CCA is a theoretically calculated value. Actual performance may vary due to test conditions.